



Privatgrund
Betreten verboten
Kein Durchgang









GMC

657

POWER PLEET 500
OHMA

ZUTRIFF
VERBOTEN
MOBLOCK MOTORS





D B AR 968 H



Privatgrundstück
Betreten verboten
Kein Durchgang

MORLOCK
MOTORS

SCHOOL BUS

Amtran





D B AR 968 H

Privatgrundstück!
Betreten verboten!
Kein Durchgang!

SCHOOL BUS

Amiran

MORLOCK MOTORS
MILITÄRFAHRZEUGE - IN FERN
Im Besonderen für: LKW, Bagger, Traktoren, etc.

**ZUTRITT NUR
FÜR BEFUGTE!**









1962

GENERAL TIRE GT









6TAGM



























































34

34

34

34

34













































CAUTION
MAXIMUM SPEED IN MPH
TRANSFER CASE
LOW
22
THIRD
SECOND
FIRST
REVERSE
+ DO NOT USE REVERSE IN

WARNING
BUZZER OPERATION AND/OR WARNING LIGHTS INDICATE AN UNSAFE DRIVING CONDITION. CHECK GAUGES BEFORE PROCEEDING.
TRANSFER CASE
TO SHIFT TRANSFER CASE, SHIFT TRANSMISSION IN TO "NEUTRAL".
SHIFT TRANSFER CASE, RETURN TRANSMISSION TO DRIVE RANGE.
CAUTION: MAXIMUM SPEED TRANSFER CASE MAY BE SHIFTED
TO LOW TRANSFER IS 20 MPH.

TOWING
ANYTIME THE VEHICLE IS TOWED, THE TRANSFER CASE & TRANSMISSION MUST BE SHIFTED TO NEUTRAL.
NOTE: ENGINE CANNOT BE STARTED PUSHING OR TOWING VEHICLE.
ENGINE START
1. PLACE TRANSMISSION IN NEUTRAL.
2. TURN BATTERY SWITCH ON.
3. TURN START SWITCH ON.

ATTENTION
CHECK FOR OBSTRUCTIONS, CLEAR COMPLETELY.
ACTUATES W/VE DAMAGED EQUIPMENT.
IN ADVANCE W/VE.
1. MAKE SURE TO INSTRUCT TO PULL W/VE.
2. ALLOW W/VE TO BE ENGAGED BY OPERATOR.
3. ALLOW W/VE TO BE RELEASED BY OPERATOR.

20 25 30 35 40
R.P.M.
40
MILES PER HOUR

0 20 40 60 80 100 120 140 160 180 200 220 240
MILES PER HOUR

FUEL
DIL
PRESS 120
SECOND

















105213

01MYS

US VV



2320-01-102-7155
129676

1826

4







SEAT BELT HAS NON-LOCKING RETRACTOR. FOR PROPER USE, BELT MUST FIRST BE EXTENDED FROM THE RETRACTOR. PRESSURE MUST BE RELEASED FROM THE RETRACTOR BEFORE BELT IS RETRACTED.

WARNING
PRIOR TO STARTING ENGAGE PARK BRAKE AND SHIFT TRANSMISSION TO NEUTRAL

Instrument cluster containing:

- Pressure gauge (0-120)
- Temperature gauge (120-240)
- Speedometer (0-60 MPH)
- Tachometer (0-1200 RPM)
- Level gauge (0-12)
- Oil pressure gauge (0-60)

Controls to the right of the gauges:

- AIR: FLOOR, LEFT SIDE, RIGHT SIDE
- TEMP: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12

SERVICING DATA		TIRE INFLATION PRESSURE		MANUALS	
FUEL TANK CAPACITY	35 GALS	FRONT	32 PSI	LUBRICATION	LO 9-220-086-12
COOLING SYSTEM CAPACITY	7 QTS + 1 QT FOR FILTERS	REAR	32 PSI	OPERATOR'S	TM 9-220-086-01
CRANKCASE CAPACITY	7 QTS + 1 QT FOR FILTERS	SPARE	32 PSI	MAINTENANCE	TM 9-220-086-01
TEMPERATURE	ABOVE +15°F	GO TO 45°F	GO TO 45°F	OPERATOR'S	TM 9-220-086-01
ENGINE OIL	SAE 15W-40	SAE 15W-40	SAE 15W-40	PARTS LIST	TM 9-220-086-01
GREASE	SAE 2	SAE 2	SAE 2		

VEHICLE BREAK-IN SERVICE
DURING THE FIRST 500 MI (804 KM) OF OPERATION:
• DO NOT EXCEED A SPEED OF 55 MPH (88 KPH)
• DO NOT DRIVE FOR LONG PERIODS OF TIME AT CONSTANT SPEED
• AVOID RAPID ACCELERATION OR DECELERATION
• DRIVE AT MODERATE SPEEDS UNTIL THE ENGINE IS FULLY WARMED UP
• NO TRAILER TOWING

MAX. VEHICLE OPERATING SPEED	
1st Gear	15 MPH (24 KPH)
2nd Gear	25 MPH (40 KPH)
3rd Gear	35 MPH (56 KPH)
4th Gear	45 MPH (72 KPH)
5th Gear	55 MPH (88 KPH)
6th Gear	65 MPH (104 KPH)
7th Gear	75 MPH (120 KPH)
8th Gear	85 MPH (137 KPH)
9th Gear	95 MPH (153 KPH)
10th Gear	105 MPH (169 KPH)
11th Gear	115 MPH (185 KPH)
12th Gear	125 MPH (201 KPH)













WARNING
PRIOR TO STARTING, ENGAGE PARK
BRAKE AND SHIFT TRANSMISSION
TO NEUTRAL

WARNING
SEAT BELT HAS NON-LOCKING RETRACTORS. FOR
WEAVING MUST FIRST BE COMPLETELY EXTENDED.
NON-LOCKING RETRACTOR DEVICE. ALL EXCESS WEAV-

ENG STOP
RUN
START

30 60 90 120
PRESS

180 200 240
TEMP

0 20 40 60 80 100 120
CROSS COUNTRY TRAILER OVERSPEED
MPH

1/4 1/2 3/4
LEVEL

14 16 18 20
VOLTS

AIR
FLOOR AIR LEFT SIDE RIGHT SIDE

TEMP
MAX

SERVICING DATA
DIESEL NO. 1
FUEL TANK CAPACITY
COOLING SYSTEM CAPACITY
CRANKCASE CAPACITY 7 QTS + 1 QT
TEMPERATURE ABOVE +15°F 140° TO
ENGINE OIL CR-10 CR-10
GEAR OIL DD 5000 CR-10
GREASE GAA

VEHICLE BREAK-IN SERVICE
DURING THE FIRST 500 MI.
(804 KM) OF OPERATION:
• DO NOT EXCEED A SPEED
OF 55 MPH (89 KM/H)
• DO NOT DRIVE FOR LONG
PERIODS OF TIME AT
CONSTANT SPEED
• AVOID RAPID ACCELE-
RATION OR DECELERATION
• DRIVE AT MODERATE
SPEED UNTIL THE ENGINE
IS FULLY WARMED UP
• NO TRAILER TOWING













OSHKOSH
MRAP

38
53

SA
СНАБЖЕНИЕ

























